
# Payload System Description

Virginia Ford

Solids pictures courtesy of Tim Ho






### **Payload System Concept Status**



- Goal of Mission Concept Development:
  - Demonstrate feasibility of a mission that meets core science needs
  - There are technical challenges
- Presentation of a Developing Concept work in progress
  - Instrument Concept Studies will help define the final approach
  - Place holder instruments do not represent preferences for final instruments - are used to aid in determining observatory capability
- There are limitations and constraints: ie
  - Launch mass and shroud volume
  - Starlight suppression stability requirements
  - Time and resources




## **Payload Mechanical Interfaces**





#### **Placeholder Science Instrument Locations**

- Not preferred choices for instrument concepts
- Used to understand accommodation requirements




Electronic Box Platform

Placeholder Instrument	Placeholder Volume (millimeters)
General Astrophysics Instrument	2250 x 1400 x 400
Planet Detection Camera	325 x 400 x 300
Planet Characterization Instrument	750 x 400 x 300



# **Science Instrument optical paths**

- From tertiary mirror of telescope, a pickoff mirror sends:
  - Outer portion of the beam to the GAI (assumed 10 arcsec 4 arcmin)
    - Beam height limitation for GAI: 30 cm
  - Inner portion of the beam to the SSS
  - Light delivered to detection and characterization instruments through SSS






#### **Payload Computing and Electronics Philosophy**



Assumed Electronic box sizes: (W x H x L) cm

- 1) OTA MCE 36 x 38 x 24
- 2) Payload System Elex 36 x 38 x 48
- 3) Laser Metrology 40 x 40 x 68
- 4) OTA Thermal Control 36 x 38 x 38
- 5) Planet characterization 36 x 38 x 36
- 6) Planet detection 36 x 38 x 48
- 7) Fine DM controller 36 x 38 x 36
- 8) GAI 36 x 38 x 24
- Planet Detection Detector electronics –
  12 x 12 x 18
- 10) Planet Characterization Detector electronics— 12 x 12 x 18
- 11) GAI Detector electronics- 12 x 12 x 36

- Instruments responsible for science data computing including data compression
- Spacecraft will provide data storage and downlink
- All instrument electronics mounted on payload side to minimize cabling stiffness (thus dynamic perturbation exchange)
- Instrument electronics not required to be colocated with optics assemblies mounted on payload-provided thermal control plate



18 March 2005

ROSES NRA TPF-C ISC Proposal Kick-off meeting

Note: Thermal enclosure not shown, SSS shown transparent blue




# **Payload Thermal Control**



- Isothermal Enclosure surrounds warm portion of payload:
  - -290K 305K
- Cold zone enclosing detectors isolated from warm zone:
  - assumed temperature: -100C±5C

Placeholder Detector	Cooling power (assumed)
GAI	12 Watts
Detection	5 Watts
Characterization	8 Watts



Terrestrial Planet Finder